





THE INFLUENCE OF DENSITY OF GAS ON THE FORMATION OF CORONA

Dissertation

Submitted to the Board of University Studies of The Johns Hopkins University in Conformity with the Requirements for the Degree of Doctor of Philosophy

By

Theodore T. Fitch

June 1913.

166,666

[illegible]

[illegible]

By T. [illegible]. Fitch.

Contents

1. Introduction.

This paper describes the results of a series of experiments on the effects of pressure, temperature, density of gas and size of conductor on the formation of corona. The study of the effect of pressure and temperature on corona forming voltage was begun by Ryan in 1904. The study was again taken up in 1909 by Watson. In 1910 Dr. Whitehead began an investigation of the corona and the work given here is largely an extension of that in the second of his series of papers on "The Electric Strength of Air". Peek has also devoted some study to these phases of the corona problem. All the observers mentioned used alternating current except Watson who worked with direct current.

The purpose of the present work has been the extension of the earlier investigations both as to range of pressure and size of conductor and also to obtain further information on the influence of temperature. Some observations were also made with carbon dioxide as the gas surrounding the conductor instead of air to see what part, if any, is played by the nature of the gas.

The larger part of the work [illegible]

of critical, or corona forming, intensity [illegible]. For this work conductors varying from [illegible] to [illegible] diameter were used, and the pressure was varied from [illegible] to 110 cm of mercury.

2. Review of Previous Work on Pressure and Temperature.

This review is confined largely to the investigations on variation of critical intensity with pressure and temperature. Some other points, however, have such an intimate relation to these variations or at least to a study of them that they will be mentioned.

It was shown by Ryan[1] that for the one size of conductor which he used the critical intensity is a linear function of the pressure from 40 to 90 cm of mercury. A similar relation was shown to hold for variations with temperature between 21 and 93°C.

Watson published a set of experiments[2] in 190[illegible] showing a linear relation between pressure and critical intensity for the case of direct currents. His range of pressures was from 300 to [illegible] cm of mercury and in size

---

1 Ryan, Conductivity of the Atmosphere at High Voltages [illegible] A. I. E. E. [illegible], 1904.

2 Electrician, Vol. [illegible], [illegible].

of conductors from .04 to .4[illegible] cm. [illegible] showing the amount of current [illegible]

In Dr. Whitehead's papers [illegible] were given showing a linear relation between critical intensity and pressure from [illegible] to 100 cm. The conductors used ranged in diameter from .122 to .475 cm. Some experiments were also made showing a linear relation between critical intensity and temperature. Only one size of conductor was used. The range of temperature was from 0 to 41° C.

It was further shown that:

The critical intensity is independent of free ionization, moisture content and velocity of the air.

The visual critical intensity is identical with that determined by an electroscope.

The critical intensity for clean round conductors for a pressure of 76 cm and temperature of [illegible]° [illegible] expressed by a formula of the form:

$$g = A + \frac{B}{\sqrt{D}} \quad (1)$$

where A and B are constants and D is [illegible] diameter [illegible] the conductor. This formula [illegible] discussed [illegible].

Peek[5] has given the results of [illegible]

[5] Peek. The Law of Corona. [illegible] A.I.E.E. [illegible], 1.[illegible]

variations of critical intensity with temperature [illegible] practically a linear law between -20 and +140° C. [illegible] also given an empirical formula covering the variations of critical intensity with change of temperature and pressure for a tube and concentric conductor as follows:

$$g = 31\,\delta\left(1 + \frac{0.308}{\sqrt{\delta r}}\right) \qquad (2)$$

where g is the critical intensity in kilo volts per cm., r is the radius of conductor and

$$\delta = \frac{3.92\, p}{273 + t},$$

p being the pressure in cm of mercury and t the temperature centigrade. So far as can be found the only statements he has given concerning the influence of pressure on the variation of critical intensity is a curve[4] giving observations on a 2.54 cm conductor for pressures from 2 to 57 cm and a table of values of δ and corresponding values of g in closing the discussion of his 191[illegible] paper[5]. No description of his methods was given.

The observations of which the results are given in this paper were [illegible] in the spring of 191[illegible] before some of Peek's work was published. It appears, however, that there is still a lack of sufficiently extensive data on [illegible]

[4] Peek: Nature of Corona. [illegible] Review, [illegible].

[5] Peek: Proc. [illegible] Nov. 1.1[illegible].

of critical corona intensity with pressure [illegible] con-
ductor.

F. Apparatus and Equipment.

For the pressure measurements a [illegible] tube about 60 cm in length was used. The ends were fitted with insulation caps about 15 cm long. These caps were for the double purpose of insulation and sealing for the variation of air pressure both above and below atmospheric. A rotary air pump enabled the tube to be evacuated to about 5 cm of mercury in 5 minutes. Most changes of pressure could be made in a minute or two, but owing to numerous joints necessary for insulation purposes there was present some leakage, which necessitated a longer time to exhaust to the lowest pressure reached; and set the limit of about 5 cm as the minimum.

A small glass window was placed in the tube for making visual observations of the corona, but during most of the work the gold leaf electroscope was used for detecting the point at which corona begins. This method has been described in detail in the first of these papers[*] [illegible] no further description is necessary here. Fig. 1 shows the general arrangement of the apparatus. The [illegible] of corona is very [illegible] [illegible].

[*] Whitehead: Trans. A.I.E.E. XXIX, 1910, p. 1159

or less in the voltage will cause the time of constant discharge to change from about a half hour to five seconds. The difference between the beginning of corona as observed by the ear and by the discharge of the electroscope is within this small error of observation.

The observations on the influence of temperature were made with a similar apparatus, except that the tube was in this case surrounded by a water jacket. Hand stirring of the water was found to be sufficient to keep the temperature of the air within the tube uniform to about two degrees. Only the smaller sizes of conductor could be used in this apparatus owing to spark over troubles occasioned by the reduced size of outer tube. The heating was done by gas burners and ice was used for getting reduced temperature.

Source of Power.

The power for all the experiments was drawn from a 10 KW., 100000 volt transformer. The transformer was operated by a motor generator set of 7.5 KW capacity, the generator field being excited by a storage battery, resulting in good voltage control. All experiments were made at a frequency of 60 cycles. The transformer is provided with a tap at [illegible] giving 150 volts for 100000 volts on the high tension

terminals as computed from the ratio of primary and secondary turns. This test coil was used entirely in making measurements of the voltage. All determinations of ratio of maximum to mean effective voltage were also obtained from this coil.

4. Ratio of Maximum to Mean Effective Voltage.

For the purpose of checking the results this ratio was determined by two methods. The first makes use of the oscillograph, the second of a rotating contactor and the principle of the potentiometer.

The ratio was determined from the oscillograms by measuring a number of ordinates, usually about 30 or 40 to a cycle. From these ordinates taken at equal distances the ratio of maximum to the square root of the mean square value was computed. The principal difficulty with this method is to obtain an oscillogram with lines sufficiently sharp and narrow.

The contactor method is indicated in Figure [illegible], the contact wheel being placed on the generator shaft. In the actual apparatus a handle was provided for reading [illegible] the point of contact. [illegible] the contact can be shifted until the [illegible] peak of the waves. Then the [illegible] is moved until the galvanometer indicates [illegible].

The readings of the [illegible] simultaneous [illegible] alt[illegible] the [illegible] volt-meters are then taken. The [illegible] in volts is the ratio desired, the direct current voltmeter indicating the maximum voltage and the alternating current voltmeter the mean effective value.

The chief difficulty with this method is to keep the source of alternating voltage sufficiently steady during the time necessary for an observation. A damped galvanometer is required of fairly high sensibility. Only a relative calibration of the voltmeters is necessary since the ratio is all that is required. The alternating current voltmeter used was of the electrodynamometer type and it was compared with the direct current voltmeter by taking the mean of readings with reversed polarity.

TABLE 1, [illegible] gives the ratio of maximum to mean effective voltage for the various voltages on the test coil of the transformer used in the experiments. The values taken from the curve were used in making reductions of readings of critical intensity.

Figure 4 is a reproduction from a typical oscillogram.

Table 1.

Test Coil Volts	Ratio = $\frac{\text{Max. voltage}}{\text{Mean eff. voltage}}$ Contractor	Oscillograph	From Curve
4		1.395	1.400
7		1.420	1.420
10		1.470	1.430
15	1.451		1.440
20	1.459		1.445
25	1.456		1.445
30	1.429		1.445
35	1.438		1.445
50	1.444	1.446	1.440
60	1.421	1.470	1.440
75	1.452	1.427	1.440

5. Variation of Critical Intensity with Pressure.

Fig. 5 shows the observed variation of critical voltage with pressure, while Fig. 6 shows the corresponding variation of critical intensity computed from the same observations. As mentioned before 5 conductors ranging from .13 to .950 cm in diameter were used. Above 50 or 60 cm pressure the curves are nearly straight; the curvature being so slight as to be within the error of observation. They explain, therefore, the conclusion of the earlier paper that the relation between pressure and critical intensity is linear in this region.

The critical intensity is the electric field at the surface of the inner conductor. Its value is given by the formula:

$$X = \frac{dV}{dr} = \frac{E}{r \log \frac{R}{r}}$$

where X is the critical intensity, V the potential, r and R the radii of inner and outer conductors respectively. This may be shown as follows:

$$X = \frac{2e}{r}$$

for an infinitely long charged conductor where e is the charge per unit length. The capacity of concentric cylinders per unit length is given by the formula:

$$C = \frac{1}{2 \log \frac{R}{r}}$$

For a given difference of potential E the charge e is given by the equation:

$$e = \quad = \frac{V}{2 \log \frac{R}{r}}$$

$$X = \frac{2e}{r} = \frac{2}{r} \cdot \frac{V}{2 \log \frac{R}{r}} = \frac{V}{r \log \frac{R}{r}}$$

Tables 2 to 10 give a complete set of observations.

Several readings were taken at each pressure as shown in the readings. The pressure was determined by use of a gauge or manometer. This method gives, of course, only the difference of pressure between that in the tube and atmospheric. For this reason it was necessary to read the barometer to obtain the absolute pressure. The voltage was read by two Weston alternating current voltmeters of suitable ranges connected to the test coil of the transformer as has been stated before. In taking readings the electroscope was first charged and then the voltage gradually raised till the electroscope was suddenly discharged as shown by the fall of the gold leaf.

6. Empirical Formulae.

As stated before, Peek has given the formula

$$g = 31\delta\left(1 + \frac{0.308}{\sqrt{\delta r}}\right)$$

connecting the critical intensity g in kilo volts per cm with pressure, temperature and radius of conductor. Figure 6 shows curves for three sizes of conductor for the temperature 25°C. As indicated the circles are observed points while the full lines are plotted from the formula given above. It is seen that as the formula stands it does not meet these conditions very closely, [illegible]

[illegible]

[illegible] 2.

[illegible]

..uge Read- ings		Diff.	Baro- meter	Temp.	Pres- sure mm	Volts on test coil Read	Cor- rected	Criti- cal ..V. max.	Criti- cal ..V. max. at 20°C	Critical Intensity ..V.
[illegible]6	997	711	766	13.3	55	4.1				
6	997	11				4.0				
6	997	11				4.0	4.3	5.0	5.0	9.[illegible]
6	997	11				4.0				
6	997	11				4.0				
[illegible]1	925	534				8.4				
[illegible]0	26	66				.5				
[illegible]0	26	66	766		180	.3	[illegible].4	10.0	[illegible]	1[illegible].[illegible]
[illegible]	27	68				.3				
[illegible]	25	65				.4				
4	882	508				1[illegible].9				
5	82	7				1[illegible].0				
4	82	8	767		270	1[illegible].9	11.0	1[illegible].[illegible]	1[illegible].1	2[illegible].1
4	82	8				10.96				
4	81	7				10.96				
18	[illegible]	408				14.1				
18	26	08	767		755	4.1	14.[illegible]	17.1	17.0	[illegible].5
17	27	10				4.1				
17	27	10				4.1				
[illegible]	762	296				17.2				
[illegible]5	764	9				7.1				
[illegible]	62	6	767		470	7.2	17.4	20.9	20.[illegible]	[illegible]
[illegible]	62	6				7.3				
[illegible]5	64	9				7.2				
[illegible]	[illegible]	204				1[illegible].7				
[illegible]	[illegible]	4	767		[illegible]	.7				
[illegible]5	[illegible]	5				.6	20.6	24.1	2[illegible].9	[illegible]
[illegible]5	[illegible]	4				.3				
[illegible]3	[illegible]	114				22.2				
[illegible]	[illegible]	6				[illegible].1				
[illegible]	[illegible]	6	766		655	[illegible].6	[illegible].[illegible]	[illegible]	[illegible]	[illegible]
[illegible]2	[illegible]7	5				[illegible].1				
-	-	-				25.1				
-	-	-	[illegible]		[illegible]	[illegible]				
-	-	-				[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
-		-				[illegible]				

Table 2 (continued)

[illegible] cm. Conductor.

	Gauge Readings	Diff.	Barometer	Temp.	Pressure mm.	Volts on test coil: Read	Volts on test coil: Corrected	Critical V. max.	Critical V. max. at 20°C	Critical Intensity [illegible]
.9	532	97				27.5				
.8	34	4	768		863	7.5	27.[illegible]	57.[illegible]	[illegible]	[illegible]
.8	34	4				7.5				
.8	34	5				7.5				
5	[illegible]	209				3[illegible].2				
5	[illegible]	10	768		[illegible]78	[illegible].2				
5	[illegible]	10				[illegible].4	30.4	[illegible]	[illegible]	[illegible]
5	[illegible]	09				[illegible].2				
5	408	107				32.7				
4	08	6				2.7				
4	09	5	768	16.9	1073	2.6	32.8	59.5	79.2	[illegible]
3	10	3				2.7				
4	09	5				2.8				

Table C

[illegible] cm connector

Gauge Readings		Diff.	Barometer	Temp.	Pressure mm	Volts on test coil Read	Volts on test coil Corrected	Critical [illegible] max.	Critical [illegible] max. at 20°C	Critical [illegible]
88	1000	712	760	1[illegible].2	48	4.1				
88	00	712				4.[illegible]				
88	00	12				.2	4.5	5.5	5.5	[illegible]
88	00	12				.2				
88	00	12				.5				
16	958	642				7.1				
16	60	4				.1				
16	60	4				.0	7.[illegible]	[illegible].8	[illegible].5	10.1
15	60	5	760		116	6.9				
16	59	3				7.1				
49	915	566				10.2				
46	15	7				.2				
48	15	7	760		195	.2	10.3	12.3	12.3	1[illegible]
48	16	8				.2				
48	15	7				.1				
562	910	549				10.9				
61	10	9				.7				
61	10	9	750	19.8	207	.7	10.9	15.0	15.0	20.0
61	1[illegible]	9				.7				
61	10	9				.6				
31	846	415				15.6				
31	46	15				.6				
31	46	15	756		341	.6	15.7	16.5	[illegible]	[illegible]
31	46	15				.6				
400	719	316				1[illegible].9				
81	801	20				1[illegible]				
85	797	12	756		441	19.0	19.[illegible]	[illegible]	[illegible]	[illegible]
84	9[illegible]	14				19.1				
84	98	14				1[illegible]				
550	[illegible]	[illegible]				[illegible]				
55[illegible]	[illegible]	15				[illegible]				
57	55	16	75[illegible]		[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
3[illegible]	54	13				[illegible]				
[illegible]	55	19				[illegible]				

Table [illegible] (contin[illegible])

.[illegible] conductor

[illegible]ure	[illegible]ead- ings	Diff.	Baro- meter	Temp.	Pres- sure mm	Volts on test coil Read	Volts on test coil Cor- rected	Criti- cal K.V. max.	Criti- cal K.V. max. at 20°C.	Critical Intensity [illegible]
[illegible]3	710	117				25.4				
[illegible]2	10	18				.5				
[illegible]1	11	20	75[illegible]		638	.4	25.5	3[illegible].7	5[illegible].7	4[illegible].[illegible]
[illegible]	1[illegible]	18				.4				
-	-	-				2[illegible].2				
-	-	-	756		756	[illegible].9	[illegible].4	[illegible].4	[illegible]5.4	[illegible]
-	-	-				[illegible]				
-	-	-				[illegible].2				
[illegible]5	5[illegible]7	158				34.0				
[illegible]5	[illegible]7	58				3.9	34.1	41.1	41.1	[illegible]
[illegible]4	[illegible]7	57	75[illegible]		[illegible]14	4.0				
[illegible]4	[illegible]7	57				3.9				
[illegible]9	[illegible]4	[illegible]5				38.[illegible]				
[illegible]0	[illegible]	[illegible]5	75[illegible]		1051	[illegible]	[illegible]	4[illegible]	[illegible]	[illegible]
[illegible]0	55	[illegible]5				[illegible]				
[illegible]0	55	95				[illegible].2				

inrs	[illegible]	[illegible]	[illegible]	[illegible]	res- sure mm	[illegible]	[illegible]	[illegible]	20°C	[illegible]
8	9[illegible]	711				4.4				
7	99	2				.3				
7	1000	3	760	18.1	48	.3	4.6	5.4	5.4	7.[illegible]
7	00	5				.5				
7	0[illegible]	7				.3				
1	951	630				[illegible].3				
1	52	31				.4				
0	52	32	760		159	.2	8.4	10.0	1[illegible]	12.9
0	55	33				.2				
1	52	31				.3				
8	910	552				11.7				
8	09	1				.7				
8	09	1	757		206	.8	11.[illegible]	14.0	14.2	18.2
8	09	1				.8				
8	09	1				.8				
0	865	475				15.3				
0	65	5				.4				
0	65	5	757		282	.4	15.5	18.7	18.6	24.[illegible]
0	64	4				.4				
0	64	4				.4				
8	[illegible]	565				20.0				
7	24	7				20.0				
[illegible]	21	1	753	17.2	75[illegible]	0.1	2[illegible].1	24.2	24.1	31.1
8	22	4				0.0				
8	762	534				25.[illegible]				
8	62	4				5.0				
8	62	4	753		519	4.9	25.0	30.1	[illegible]	[illegible]
7	62	5				4.7				
8	61	3				4.6				
7	713	130				2[illegible].6				
5	15	30				[illegible].4				
7	17	26	753		626	[illegible].5	[illegible].6	[illegible].4	[illegible].2	[illegible]
7	12	26				[illegible].5				
7	12	26				.5				

Table 4 (continued)

.400 cm collector

Gauge Readings		Diff.	Barometer	Temp.	Pressure mm.	Volts on test coil Read	Corrected	Critical V. Gr. Mean	at 20°C	Critical Intensity, ..., c. .
-	-	-				33.5				
-	-	-				3.1				
-	-	-	752		752	3.1	33.2	40.0	[illegible]	31.3
-	-	-				3.0				
-	-	-				3.0				
97	757	160				[illegible].2				
97	57	60				9.4				
97	56	59	755		915	9.0	39.1	40.9	40.6	[illegible].2
97	57	60				[illegible].0				
36	341	335				44.7				
36	73	7				[illegible].0				
36	73	7	755		1069	5.0	44.9	54.0	55.6	[illegible].5
37	73	6				4.9				

Table 5.

[illegible]

Gauge Readings		Diff.	Barometer	Temp.	Pressure mm	Test Coil Volts Read	Test Coil Volts Corrected	Critical ... Max. Read	Critical ... Max. at 20° C.	Dielectric Strength ...
0	964	[illegible]4	757	2[illegible].2	75	[illegible].0				
0	64	4				.0				
0	64	4				.0	[illegible].2	[illegible]	[illegible]	[illegible]
0	64	4				.0				
0	64	4				.0				
5	949	624				9.2				
5	49	4				.2				
4	49	5	757		104	.0	9.3	11.1	11.1	1[illegible]
6	46	0				.2				
0	913	503				12.4				
0	12	2				.4				
0	13	3	757		194	.4	12.5	15.0	15.0	1[illegible]
9	14	5				.7				
0	15	3				.4				
1	918	467				17.1				
0	19	69				16.9				
0	19	69				.9	17.2	2[illegible].7	2[illegible].5	[illegible]
1	17	68				7.1				
2	825	303				24.0				
2	25	3	749		446	4.2	24.1	[illegible].1	28.6	3[illegible]
1	25	4				4.1				
1	26	5				4.2				
4	741	177				30.2				
3	42	59	749		590	.1	30.2	36.4	36.0	4[illegible]
3	43	60				.1				
3	41	59				.1				
	–	–				37.1				
	–	–				7.0				
	–	–	749		749	[illegible].9	[illegible].9	44.[illegible]	[illegible].1	....
	–	–				[illegible].7				
	–	–				[illegible].7				
5	[illegible]	210				45.5				
5	25	10	749		978	4[illegible].2				
5	26	09				[illegible].4	[illegible].4	54.5	[illegible]	[illegible]
5	27	08				[illegible]				
2	485	097				49.5				
2	86	96				.1				
2	85	97	749		[illegible]	.7	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]				[illegible]				

Table [illegible].

[illegible] er [illegible]ter.

[illegible]	[illegible]	[illegible].	Baro-meter	Temp.	Pres-sure mm	Test Coil Volts [illegible]	Test Coil Volts Cor-rected	Critical V. Max. [illegible]	Critical V. Max. at 25° C.	[illegible]
73	[illegible]	678	750	18.5	73	6.9				
72	51	9				7.0				
73	51	8				7.0	7.2	8.5	8.4	[illegible]
73	51	8				7.1				
21	962	541				14.9				
22	62	40			216	15.1	15.1	18.[illegible]	1[illegible].[illegible]	1[illegible].4
22	61	39				5.0				
22	61	39				5.1				
[illegible]6	920	464				1[illegible].9				
[illegible]	20	5				.8	1[illegible].[illegible]	[illegible].1	[illegible]	[illegible]
[illegible]	18	2			294	.8				
[illegible]	17	0				19.0				
56	17	1				9.0				
26	[illegible]25	[illegible]9				[illegible].7				
27	24	7				6.3	[illegible].3	[illegible].[illegible]	[illegible]1.9	[illegible]
27	25	8			457	6.6				
25	26	301				6.6				
39	[illegible]41	152				[illegible].4				
38	43	5				[illegible].[illegible]				
38	42	4			601	[illegible].5	73.4	4[illegible].2	[illegible]	4[illegible].6
36	44	8				3.2				
38	42	4				[illegible].3				
–	–	–				40.3				
–	–	–			750	[illegible].7	4[illegible].3	4[illegible].6	4[illegible].1	4[illegible].1
–	–	–				[illegible].2				
–	–	–				[illegible].2				
[illegible]5	[illegible]1	1[illegible]4				47.3				
[illegible]	[illegible]	5				7.4				
[illegible]	[illegible]	6			[illegible]11	7.4	4[illegible].[illegible]	[illegible]	[illegible].4	[illegible]
[illegible]	[illegible]	4				7.3				
[illegible]	[illegible]14	[illegible]				[illegible].[illegible]				
[illegible]	13	4			991	[illegible].8	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	11	7				[illegible].1				
[illegible]	[illegible]1	7				.3				
[illegible]	[illegible]	6				.[illegible]				

Table 4.

. . . . . [illegible]ometer

Gauge Readings		Diff.	Barometer	Temp.	Pressure mm	Test Coil Volts: Read	Test Coil Volts: Corrected	Critical V. Max.: [illegible]	Critical V. Max.: . C	[illegible] Strength [illegible]/cm
00	982	082	757	20.2	75	6.8				
00	82	2				.8	7.0	[illegible]	.3	7.0
99	82	[illegible]				.[illegible]				
99	82	3				.[illegible]				
24	948	624				10.6				
24	47	3				.5				
24	47	3	757		154	.6	10.7	1[illegible].6	[illegible]	11.[illegible]
24	46	2				.6				
24	46	2				.7				
49	913	564				14.1				
49	13	4	757		195	.2	14.2	17.1	17.1	15.7
49	13	4				.1				
49	13	4				.1				
49	14	5				.2				
71	371	460				19.8				
71	31	60				.7				
72	31	59	748	16.4	338	.9	20.1	24.2	24.0	22.0
71	31	60				.8				
71	31	60				.8				
37	745	308				28.0				
35	46	11			441	7.9				
37	43	06	749			8.0	28.1	32.9	32.6	30.[illegible]
37	44	07				8.1				
36	45	09				8.0				
96	061	165				35.5				
96	61	65	749		585	5.4	35.4	42.7	42.5	[illegible]
97	60	63				5.4				
97	59	62				5.5				
–	–	–				43.4				
–	–	–	750			3.3	43.5	52.2	51.7	47.5
–	–	–				3.4				
–	–	–				3.2				
21	430	141				50.5				
22	30	2				.4				
21	31	0	750		[illegible]1	.4	50.5	[illegible].5	[illegible]	[illegible]
21	31	0				.4				
21	30	1				.1				
36	415	251				[illegible]				
36	15	1	750		1002	[illegible].7				
33	13	5				[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

[illegible] 8.

.712 [illegible] meter.

[illegible] Readings		Diff.	[illegible]rometer	Temp.	Pressure mm	Coil Volts Read	Coil Volts Corrected	[illegible] Read	At 2[illegible] °C	Critical [illegible] cm
97	989	892	756	14.[illegible]	64	[illegible].8				
97	8[illegible]	[illegible]				.7				
97	89	[illegible]				.[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
97	[illegible]	2				.9				
96	[illegible]	5				.[illegible]				
80	[illegible]1	[illegible]				1[illegible].1				
79	[illegible]	[illegible]				.0				
81	7[illegible]	497	756		256	.2	19.[illegible]	[illegible].4	[illegible].1	1[illegible]
80	7[illegible]	[illegible]				.1				
80	7[illegible]	[illegible]				.2				
20	829	409				24.4				
20	29	9				4.4				
19	30	11			347	4.1	24.4	[illegible].4	[illegible].0	[illegible]
20	29	0[illegible]				4.4				
20	[illegible]	09				4.4				
[illegible]5	709	304				[illegible].0				
05	09	4				0.0				
05	[illegible]	4			452	2[illegible].9	[illegible].1	[illegible]	[illegible]	[illegible]
05	09	4				30.[illegible]				
04	09	5				[illegible].0				
09	708	199				[illegible].0				
08	0[illegible]	201				[illegible].5				
08	09	1			55[illegible]	5.7	[illegible].0	[illegible].9	42.5	[illegible].1
07	10	3				5.5				
08	09	1				5.6				
48	653	105				4[illegible].[illegible]				
48	53	5				0.9				
48	52	4			652	0.9	4[illegible].9	[illegible]	45.5	[illegible]
49	51	2				1.0				
48	53	5				0.6				
-	-	-				4[illegible].5				
-	-	-				0.5				
-	-	-			75[illegible]	0.5	4[illegible]	5[illegible]	[illegible]	46.[illegible]
-	-	-				0.4				
-	-	-				0.5				
40	[illegible]	[illegible]				5[illegible]				
40	[illegible]	[illegible]				[illegible].5				
40	[illegible]	[illegible]			[illegible]70	[illegible].5	[illegible].0	[illegible].1	[illegible]	[illegible]
40	1[illegible]	[illegible]1				[illegible]				
82	4[illegible]	[illegible]4				[illegible].0				
82	59	[illegible]				.[illegible]				
81	[illegible]	[illegible]			[illegible]	.[illegible]	[illegible].9	[illegible].5	[illegible].5	[illegible]
85	57	6				.				
85	5[illegible]	6				.				

[illegible]

Table [illegible].

[illegible]

Gauge Readings		Diff.	Barometer	Temp.	Pressure mm.	Test Cell Volts Read	Corrected	Critical V. Read	at 20°C	Critical Intensity V./cm.
77	957	680				.1		.1		
77	57	80	759	18.0	79	.2	[illegible]	[illegible]	[illegible].7	7.6
77	57	80				.2				
77	57	80				.2				
08	918	910				19.2				
08	18	10				.1				
08	18	10			149	.1	13.1	[illegible].7	17.[illegible]	[illegible]
07	1[illegible]	12				.0				
08	16	10				.2				
41	875	534				18.1				
41	75	4				.1				
41	75	4			225	.1	16.4	22.2	22.1	17.[illegible]
41	74	3				.2				
41	74	3				.2				
00	797	297				26.5				
00	96	6				6.7				
00	96	6			302	6.6	26.8	[illegible]	72.1	25.5
00	.7	7				6.7				
99	98	9				6.4				
40	742	302				38.1				
41	40	299				[illegible].1				
40	45	303			477	[illegible].9	32.1	37.7	37.5	3[illegible].4
40	43	3				[illegible].9				
40	43	3				[illegible].9				
80	[illegible]7	207				[illegible]				
80	88	8				.5				
79	[illegible]	[illegible]			[illegible]	.4	37.4	41.1	4[illegible]	[illegible].4
80	[illegible]	0				.5				
80	90	0				.5				
20	330	110				[illegible]				
[illegible]	30	0				[illegible]				
19	31	2			[illegible]	[illegible]	4[illegible].7	51.2	5[illegible].9	[illegible]
1[illegible]	[illegible]	2				[illegible]				
2[illegible]	2[illegible]	09				[illegible].7				
–	–	–				4[illegible]				
–	–	–				[illegible]				
–	–	–			[illegible]	[illegible]	4[illegible]	[illegible]	[illegible]	[illegible]
–	–	–				[illegible]				
–	–	–				[illegible]				
12	[illegible]	[illegible]				[illegible]				
1[illegible]	[illegible]	[illegible]			[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
12	[illegible]	[illegible]				[illegible]				

Table [illegible].

.[illegible] [illegible]

Gauge Readings		Diff.	Barometer	Temp.	Pressure mm	Cort Coil Volts Read	Cort Coil Volts Corrected	[illegible]	At 20°C	Int [illegible]
1	963	682				[illegible].8				
0	83	83				.7				
1	81	80	750	16.8	60	.7	7.9	[illegible]	[illegible]	[illegible]
1	81	80				.8				
0	82	82				.7				
5	937	602				14.2				
5	37	2	750		148	.1	14.2	17.1	17.0	11.9
5	37	2				.1				
0	882	502				22.1				
0	882	2				1.7				
0	82	2			249	1.7				
0	82	2	750			1.5	21.9	26.4	26.2	18.5
0	80	0				2.0				
9	80	1				1.8				
4	325	401				28.5				
4	24	0				8.2				
4	24	0	750		350	8.2	28.5	34.5	34.0	[illegible]
4	23	399				8.5				
4	23	99				8.5				
8	765	297				35.0				
7	66	9	750		463	5.0	35.0	42.2	41.9	[illegible]
8	65	7				5.0				
8	65	7				5.0				
38	738	[illegible]				[illegible]				
37	38	1				7.9				
37	38	1	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
38	36	46				[illegible]				
38	36	46				[illegible]				
-	-	-				[illegible]				
-	-	-				[illegible]				
-	-	-	[illegible]	[illegible]		[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
-	-	-				[illegible]				
-	-	-				[illegible]				

is brought into close agreement.

Figure 9 is plotted from the formula:

$$g = 33.6\,\delta\left(1 + \frac{0.[illegible]}{\sqrt{\delta r}}\right) \qquad (2)$$

The circles show the observed points as before. It is seen that with the formula so changed it represents the observations about as closely as the readings can be taken. This formula gives zero voltage for zero pressure provided r has a value greater than zero which, of course, it has for any real case. As the present observations run only as low as 4 or 5 cm pressure, they furnish no test on this point. Investigations are now under way to determine what becomes of the corona at very low pressures.

If in equation 2 the value of δ at 76 cm pressure and temperature [illegible]0° be substituted the following formula is obtained:

$$g = 34 + \frac{11.[illegible]}{\sqrt{D}} \qquad ([illegible])$$

This formula gives the variation of critical intensity with size of conductor at standard temperature and pressure. The curve in Fig. 7 is a plot from this equation while the circles are observed points. In Dr. Whitehead's work a formula of the same form but with different constants was given, namely:

$$g = [illegible] + \frac{1[illegible].[illegible]}{\sqrt{D}} \qquad ([illegible])$$

The first constant of formula (4) is [illegible] the formula (3) while the second is greater, so the [illegible] is largely one of curvature. What difference there is over the range of conductors observed is accounted for by a small discrepancy in the ratio of transformation of the transformers used in the earlier experiments and the present ones. It was found by trial in Dr. Whitehead's experiments that the indicated critical intensity with the 70000-volt transformer with which those experiments were conducted was 16 K. V. for a .147 cm conductor and 12.4 for the 100000-volt transformer which was used in the present set of experiments. These two differing values were obtained at the same time and with voltage from the same generator. Allowing for this discrepancy the present observations are brought into close agreement with the other values. As the purpose of this work is the investigation of the influence of density of gas on critical corona intensity, and as the above discrepancy does not affect the results relatively, its elimination has been left to later observations.

7. Variation of Critical Intensity with Temperature.

The curves of Fig. 10 show the variation of [illegible]

[illegible]

[illegible]

plotted. [illegible] :

$$g = [illegible]\,\delta\left(1 + \frac{[illegible]}{\sqrt{\delta [illegible]}}\right)$$

Table [illegible].

Diam. of Conductor	Temp. °C	Barometer	Test Coil Volts: Read	Test Coil Volts: Corrected	Critical Intensity: Obs.	Critical Intensity: Com.
.238	4.0	758	22.6	22.6	60.3	[illegible]
	24.3	760	21.5	21.5	57.5	[illegible]
	55.4	754	19.8	20.0	55.5	[illegible]
.315	3.7	758	26.4	26.4	57.6	[illegible]
	24.2	760	25.0	25.0	54.3	[illegible]
	50.8	754	23.1	23.3	50.7	[illegible]
.399	6.3	758	29.1	29.1	53.7	[illegible]
	24.2	760	28.1	28.1	51.[illegible]	[illegible]
	51.0	754	27.9	[illegible]	[illegible]	[illegible]

The diameter of tube used as outer conductor in these experiments was 10.[illegible] cm. The curves in Fig. 9 are [illegible] straight lines [illegible] range of temperature [illegible] not [illegible] to bring out any curvature. The agreement with the [illegible] Peek equation is also very close [illegible].

[illegible]. Influence of Density of the Medium on Critical Intensity.

A simple calculation from the gas equation

$$pv = R T$$

shows that the pressure coefficient and temperature coefficient interpreted in terms of the change in volume of unit mass of gas are the same. In other words the critical corona intensity in air varies nearly as the density whether such change is produced by a change of pressure or temperature. This idea is implicitly stated in Peek's equation in his density factor . It must be remembered, however, that his definition gives only the relative density. With a view to the more definite measurement of density as the mass per unit volume we have made some interesting preliminary observations on the corona in gas heavier than air.

In Fig. 11 are shown two curves of the variation of critical intensity with pressure, one in air and the other in a mixture of carbon dioxide and air, but containing about 90% by volume of the former. Owing to the shape of the tube it was not possible to fill it with pure CO_2.

It is seen that there is little change due to the presence of the CO_2 although its density is about 1.[illegible] [illegible]

that [illegible] in. [illegible] at [illegible]

variation of critical intensity [illegible], [illegible], [illegible]

on the density, [illegible] [illegible] of the [illegible]

of the molecules [illegible], [illegible] [illegible]

[illegible] the number of molecules in [illegible] [illegible]

[illegible] function of the pressure [illegible] [illegible], [illegible]

[illegible] depend on the nature of the [illegible]. [illegible] indication

[illegible] is thus [illegible] relation [illegible] electric

intensity [illegible] is found in the average [illegible]

[illegible] molecules. This is in fact a principle tenet of

the theory of secondary ionization or ionization by collision

[illegible] explaining all forms of spark discharge in gases. A

further study along this line may throw considerable light

on some phases of the corona problem which are still obscure.

9. Comparison with Results on Sparking Potentials.

Figure 14 is reproduced from a paper by [illegible]tson on "The Dielectric Strength of Air"[*]. The curves show the variation of the sparking potential between spheres with variation of pressure. The pressures range from atmospheric [illegible]

---

[*] Jour. Inst. Elec. Engrs. Vol. 4[illegible], [illegible].

upward so that they are not directly comparable with pressures in the present set of corona experiments. From the work of other observers, however, it is known that the curves tend down toward the zero until they reach the so called "critical pressure". Upon further reduction of pressure the curves turn sharply upward. These critical pressures vary with the length of spark gap, ranging from 3.0 to 0.5 mm for spark gaps of 1 to 10 mm, respectively[6].

It is seen by reference to the curves that their general shape is the same as for critical corona intensity. The chief question of interest in both cases is the departure from the linear law as the curvature is probably due to common cause. By analogy with curves for sparking potentials it may be anticipated that the critical corona intensity may rise at very low pressures, in fact it is known that it is difficult to get the [illegible] to discharge at very high vacua.

The results obtained with corona in carbon dioxide were to be anticipated from Paschen's law. This law states that the sparking potential depends on the product of the pressure and the spark length. Curves plotted with products of pressure and spark length as abscissae [illegible] po-

---

[6] Conduction of Elec. Through Gases, J. J. Thomson, [illegible].

text. Its ordinates are nearly the same for air [illegible] dioxide but differ considerably for hydrogen. No attempt was made to try hydrogen in the present set of experiments as the medium surrounding the conductor owing to the presence of some leakage of the tube which might have resulted in the production of an explosive mixture. It is interesting to note the simplicity of the corona apparatus [illegible] that for studying the theory of gaseous conduction.

Discussion.

As most of the observed laws of corona formation are in accord with the theory of ionization by collision, a brief statement of some of the fundamental experiments and conclusions of that theory will not be out of place.

When two parallel conducting plates are connected to a source of potential difference and the gas between them ionized by X rays or radium, it is found that a current passes. This current increases at first as the potential difference is increased, but later attains a stationary value. No further increase of the current with increasing voltage is noted until a considerably higher voltage is reached when the current again increases rapidly with increasing voltage. The interpretation of this phenomenon is that the [illegible] ions [illegible] to [illegible]

current which [illegible] ions [illegible] limit. [illegible] of [illegible] this limit. [illegible], however, the volt[illegible] becomes sufficiently high the ions attain a velocity which enables them to produce new ones by collision with neutral atoms. This is known as ionization by collision or secondary ionization. This theory of ionization by collision accounts for the order of magnitude of the critical corona voltage which in the limiting case of plane surfaces is approximately 30 K.V. per cm. The mean free path of the electrons is about [illegible] x 10^{-5} cm at 76 cm pressure and 20°C as has been shown by Townsend and others. This is about [illegible] times the mean free path of the molecules of the gas. For the ordinary sizes of conductors the voltage over a mean free path of an electron is about [illegible] volts. This indicates that the critical intensity is that which gives the ionizing voltage of about 10 volts[1] in [illegible] times the mean free path, or in other words some of the electrons having a free path of [illegible] or more times the [illegible], start the corona.

The ionization theory fails to show why the critical intensity varies with the size of conductor and why the variation of critical intensity with pressure does not [illegible]

[1] [illegible]hor. [illegible], P.11.

follow [illegible] linear law. As [illegible] apparently [illegible], [illegible] critical intensity rises quite rapidly as the size of the conductor is reduced. The intensity in the gas falls away as $\frac{1}{r}$ where r is the distance from the center of the conductor, and from this it is seen that the intensity diminishes much more rapidly in the immediate neighborhood of a small conductor than a large one. Nevertheless the diminution in a distance of 5 or 10 mean free paths of an electron is negligibly small in any practical case.

The corona begins and ends at approximately the same voltage on the emf wave. This indicates that the rate of recombination of the ions is very great. It appears possible from this fact that the corona will not start until the intensity is high enough over some depth such as half a mm on account of the great amount of recombination which goes on in the neighboring space, where the intensity is too low.

Conclusions.

1. The critical corona forming electric intensity in air has been determined over the range of pressure [illegible] cm to 10[illegible] cm of mercury, for 9 sizes of round conductors of diameters from .[illegible] to .95 cm.

[illegible] few observations [illegible] in [illegible] range of 5° to 5[illegible]° [illegible] recorded.

3. [illegible] results are in substantial [illegible] [illegible] empirical relation between electric intensity, pressure and temperature suggested by Peek.

4. Experiments with carbon dioxide indicate that the critical corona intensity is independent of the absolute density of the gas, but depends on the number and spacing of the molecules, in accord with the theory of secondary ionization.

11. Bibliography.

Steinmetz: Dielectric Strength of Air. Trans. A.I.E.E., XV, 189[illegible].

Scott: High Voltage Power Transmission. Trans. A.I.E.E. XV, 1898.

Ryan: Conductivity of Atmosphere at High Voltages. Trans. A.I.E.E. XXIII, 1904.

[illegible]ershon: High Voltage Measurements at Niagara. Trans. A.I.E.E. XXVII, 190[illegible].

Balch: 30000-Volt Transmission Line. [illegible]

[illegible]echt: A 500000-Volt [illegible] Line. Electrotech[illegible] Anzeiger [illegible]

[illegible]on: [illegible] Elec. [illegible]

[illegible]tson: Atmospheric Loss under Continuous Current. Electrician, [illegible]

Dielectric Strength of Compressed Air. Jour. [illegible]

[illegible] aciol[illegible]: [illegible] . . . . .
XLVIII, [illegible].

[illegible]: [illegible]ruptive [illegible]
[illegible] 44, [illegible].

[illegible]: Disruptive [illegible] Air.
[illegible], [illegible].

Whit[illegible]: [illegible]electric Strength of Air. I, II, I[illegible].
Trans. [illegible], 191[illegible], 1.1[illegible], [illegible].

Peek: The Law of Corona [illegible] Dielectric [illegible]
of Air. I and II, Trans. [illegible]
191[illegible], 1912.

Th[illegible] Nature of Corona. [illegible], [illegible] 1.1[illegible].

[illegible], [illegible]: [illegible].
Electrotec[illegible]. [illegible], 1.1[illegible].

[illegible]r: [illegible] Pressure [illegible] conditions.
Zeitschr. [illegible].
1[illegible], 1.11.

[illegible]st: [illegible].
3[illegible], 1.11.

acioli: [illegible] Lines.
[illegible], 1.11.

[illegible]ichler: Zur [illegible]rechnung der Koronaverluste.
Electrotechn. und Maschinenbau,
[illegible] 1[illegible], 1.1[illegible].



Corona Tube Apparatus.

Fig 1.



Oscillogram at 60 volts and 60 cycles.

Fig. 4.

Biographical Note.

Theodore Thornbur Fitch, son of Henry H., and Elizabeth Fitch was born in Sac County, Iowa, September 23, 18[illegible]. In 1898 he graduated from Sac City Institute, a college preparatory school. He spent the year of 1899-00 at the State University of Iowa, and the following scholastic year entered Iowa State College where he graduated in the course in Civil Engineering in 1903. He spent the year following in the U. S. Coast and Geodetic Survey. The following year, 1904-1905 he took up the study of Electrical Engineering at Iowa State College. Since 1906 he has been continuously on the staff of the Bureau of Standards at Washington, D. C., being now an Assistant Physicist. In 1910 he took up graduate work at Johns Hopkins University choosing Physics as principal subject and Mathematics and Astronomy as subordinate subjects. He took lectures under Professors Ames and Whitehead and Drs. [illegible]son, Cohen and Pfund. He also took a number of lecture courses given at the Bureau of Standards by Drs. [illegible], Pfund and Buckingham.